Report CG-M-11-81

LEVEL

U.S. Department of Transportation

United States Coast Guard



10 (00

00 00

AD A 1 0

INSPECTION GUIDE FOR REINFORCED CONCRETE VESSELS

> INSPECTION GUIDE Volume 1

> > A. E. Fiorato L. S. Johal

Construction Technology Laboratories A Division of the Portland Cement Association

> FINAL REPORT **OCTOBER 1981**



Document is Available to the U.S. Public through the **National Technical Information Service** Springfield, Virginia 22161

12 28 023

昌

The state of the s

1. Report No.	2. Government Acces	LUAD NA	1 800	ipient's Cetelog	Na .	
		-	1	ipioni i Cololog		
CG-M-11-81	HU- 11.7	08 885				
4. Title and Subtitle Inchestion Cuide for Boinfo			3	ert Date		
Inspection Guide for Reinfo Volume 1 Inspection Guide	rced Concrete	vessers		ber 1981		
			O. Peri	ormina Organizat	ion Code	
			8. Peri	orming Organizat	ion Report No.	
7. Author's)			7			
A. E. Fiorato and L. S. Joh	al					
9. Performing Organization Name and Addre			10. 70	rk Unit No. (TRA	15)	
Construction Technology Lab A Division of Portland Ceme	oratories		 11 			
5420 Old Orchard Road	nt Association			ntract or Grant N	_	
Skokie, Illinois 60077				-CG-832171- oe of Report and i		
12. Sponsoring Agency Name and Address			''''	e or keport and	Period Covered	
Commandant (G-MMT-4/TP13)						
United States Coast Guard						
2100 Second Street, S.W.			14. Spo	nsoring Agency (ode .	
Washington, DC 20593						
Training Course for U.S. Coal 16. Abstract This guide provides a check the inspection of reinforced to insure quality of newly oversels. Topics covered inconcreting, inspection during hardened concrete, in-services.	list for use to concrete vesseonstructed vestude materials of concreting.	by U.S. Coast sels. It prov ssels and prop s, batching an Inspection af	Guard Modes it der main der con Acces MTIS DTIC Unenr Justi By Distr	emized requirements of the secreting, the secreting of th	uirements in-service ion before esting	
			Avai	lability C		
				Avail and/	70	
			1			
			Dist	Special		
			Dist			
			Piar			
			P			
17. Key Words Barges, Concrete (prestresse (reinforced), Concretes, Con Inspection, Offshore Structu Control, Ships	struction,	18. Distribution Sta	A			<u>.</u>
Barges, Concrete (prestresse (reinforced), Concretes, Con Inspection, Offshore Structu	struction,		P		22. Price	
Barges, Concrete (prestresse (reinforced), Concretes, Con Inspection, Offshore Structu Control, Ships	struction, res, Quality	sif. (of this page)	P	Special		

Form DOT F 1700.7 (8-72)

Reproduction of completed page authorized 7 1 5

TABLE OF CONTENTS

		Page
TEC	HNICAL REPORT DOCUMENTATION PAGE	i
TAB	LE OF CONTENTS	ii
1.	INTRODUCTION	1
	1.1 Format of Guide 1.2 Use of Guide	2 3
2.	VESSEL DATA	4
3.	PRELIMINARY INSPECTION	5
4.	MATERIALS	6
	4.1 Cement 4.2 Aggregates	6 8
	4.3 Mixing Water	11
	4.4 Admixtures 4.5 Reinforcing and Prestressing Steel	12 13
	4.6 Post-Tensioning Ducts	16
	4.7 Grout for Bonded Tendons	17
	4.8 Inserts and Embedments	19
	4.9 Concrete	20
5.		21
6.	INSPECTION BEFORE CONCRETING	25
	6.1 Reinforcement	25
	6.2 Prestressing Tendons	28
. .	6.3 Formwork and Embedments	30
•-	6.4 Construction Joints	32
7.	INSPECTION DURING CONCRETING	33
8.	INSPECTION AFTER CONCRETING	37
.1	8:1 Finishing, Curing, and Formwork Removed	37
	8.2 Control Tests of Hardened Concrete	39
	8.3 Post-Tensioning and Grouting	40
		4-
7.	IN-SERVICE INSPECTION	43
10.	IN SITU TESTING OF HARDENED CONCRETE	46
11	DWDAIDC	50

TABLE OF CONTENTS (Continued)

	Page
APPENDIX A - APPLICABLE ASTM STANDARDS	Al
APPENDIX B - STANDARDS, GUIDES, AND RECOMMENDED PRACTICES OF THE AMERICAN CONCRETE INSTITUTE	Bl
APPENDIX C - OTHER APPLICABLE STANDARDS, GUIDES, AND RECOMMENDED PRACTICES	Cl
APPENDIX D - ABBREVIATIONS	Dl

U.S. COAST GUARD

INSPECTION GUIDE FOR

REINFORCED CONCRETE VESSELS

1. INTRODUCTION

This Guide provides U.S. Coast Guard Marine Inspectors with a detailed check list of items to be considered for quality assurance of construction of reinforced concrete vessels and for in-service inspection of vessels. It is recognized that, within the regulatory role of the U.S. Coast Guard, the Marine Inspector does not serve to perform quality control tests for the vessel owner or contractor. However, it is necessary for the Inspector to monitor construction operations and to participate in in-service inspections so that he may determine if the condition of the vessel is satisfactory to insure safety of life and property at sea.

It is anticipated that general inspection and monitoring operations for reinforced concrete vessels will be similar to those for steel vessels. However, inspection of concrete vessel construction may require a greater level of effort. This is because concrete is essentially "manufactured" on site.

This guide is supplemented by a separate document entitled "Commentary on Inspection Guide for Reinforced Concrete Vessels," that provides background information for topics covered. It is assumed that Inspectors using the guide have knowledge of the fundamentals of concrete technology and reinforced and prestressed concrete.

Material in the guide is based on current practice for concrete in marine environments. The following publications have served as a basis for much of the material:

- (a) ACI Committee 357, "Guide for the Design and Construction of Fixed
 Offshore Concrete Structures," American Concrete Institute, 1978.
- (b) ACI Committee 318, "Building Code Requirements for Reinforced Concrete (ACI 318-77)," American Concrete Institute, 1977.
- (c) "Rules for the Design, Construction, and Inspection of Offshore Structures," Det Norske Veritas, 1977.
- (d) "Guidelines for the Design, Construction, and Classification of Floating Concrete Structures," Det Norske Veritas, 1978.
- (e) "Recommendations for the Design and Construction of Concrete Sea Structures," Federation Internationale de la Precontrainte, Third Edition, 1977.
- (f) ACI Committee 301, "Specifications for Structural Concrete for Buildings," American Concrete Institute, 1975.
- (g) "Inspection, Maintenance and Repair of Concrete Offshore Structures,"

 Cement and Concrete Association, London, 1974.

Data in these publications were supplemented with information from references listed in Appendixes to this Guide.

1.1 Format of Guide

The Guide is presented as a detailed checklist. Primary objective of the list is to insure that items critical to quality assurance are monitored by U.S. Coast Guard inspection. Data in the checklist are not intended to supercede construction specifications and drawings. These documents should be closely examined prior to start of construction.

The frequency of U.S. Coast Guard inspection will depend on a number of factors including size and complexity of the project, experience and performance record of the contractor, experience and performance record of the testing laboratory, and experience of the Marine Inspector. The level of inspection effort will vary at different stages of construction. After

verification of test procedures, documentation, and flow of reports, the Coast Guard Marine inspector may choose to monitor daily test reports, and only spot-check field operations. Although the inspector may not verify all items on the checklist, he should be certain that they have been considered in the construction process.

1.2 Use of the Guide

The Inspector's initials and the date of inspection should be entered after an item on the list has been verified. If the item is not applicable, the letters "NA" should be entered. If no entries appear after an item, it is assumed that the Inspector is not satisfied with the inspection results and that corrective measures are being taken. At the Inspector's option, corrective measures to be taken may be noted in the guide. Reinspection of an item may be indicated by entering initials and the new date in a different color.

Items marked with an asterisk (*) generally require inspection on a regular basis. Frequency of inspection will be based on specific requirements of each project.

Numbers of Sections 4 through 11 correspond to companion sections in the "Commentary on Inspection Guide for Reinforced Concrete Vessels."

2. VESSEL DATA

			
		····	 <u></u>
			
			
·			

3. PRELIMINARY INSPECTION

	CHECK LIST	INITIALS	DATE	NOTES
1.	Have design and drawings been approved by USCG Merchant Marine Technical Branch?	wagitti i portifi nalayan		
2.	Have plans and specifications been reviewed by inspector prior to start of construction?	v-Mahadhaja		
3.	Has a preconstruction conference been held with USCG, Owner, Clas- sification Society, Contractor, Testing Laboratory, and other interested parties to review construction specifications and to coordinate inspection operations?			
4.	Have representatives been assigned for coordination of inspection between USCG, Owner, Classification Society, Contractor, Test Laboratory, and other interested parties?			
5.	Have provisions been made for flow of records and .eports?	The state of the s		
6.	Does the Testing Laboratory(ies) meet requirements of ASTM E329?			
7.	Has the Testing Laboratory(ies) been inspected by the Materials Reference Laboratory?			

4.1 Cement

		CHECK LIST	INITIALS	DATE	NOTES
1.	asth	portland cement conform to 1 C150 Type I, II, or III; or 1 C595 Blended Hydraulic Cements?			
2.	repo	certified copies of mill test orts for cement included with shipment as follows:			
	(a)	Chemical Analysis (ASTM C114)			
	(b)	Fineness by Turbidimeter (ASTM C115) or Fineness by Air Permeability (ASTM C204)	-		
	(c)	Autoclave Expansion (ASTM C151)			
	(d)	Time of Setting by Vicat Needle (ASTM C191) or Time of Setting by Gillmore Needles (ASTM C266)		-	
	(e)	Air Content of Mortar (ASTM C185)			
	(£)	Compressive Strength (ASTM Cl09)			
	(g)	False Set (ASTM C451) - Optional			
	(h)	Heat of Hydration (ASTM C186) - Optional			
3.	(C ₃ A	ricalcium aluminate content) within limits stated in truction specification?			
4.	test	ncoming cement sampled and ed to verify supplier's ifications?			
5.	and	ddition, are tests ASTM Cl09 ASTM Cl91 repeated monthly to k quality of cement in storage?			
6.	show	ement is packaged, is it marked ing type, brand, date of ipt, and manufacturer's name?			

4.1 Cement (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
7.	Is packaged cement protected from weather during shipment and storage?		•	
8.	Is packaged cement used in the chronological order that it was delivered?			
9.	Is bulk cement stored in weather- tight bins or silos?	a responsability distribu		
10.	Are controls adequate to identify bulk cement?			
11.	Are there individuals responsible for receiving, inspecting, storing, and handling cement?			
12.	Are records available on all of the above items?			

4.2 Aggregates

		CHECK LIST	INITIALS	DATE	NOTES
1.	Do a or C	ggregates conform to ASTM C33 330?			
2.	from	here more than one (1) location which aggregate is obtained are tests made from each?			
3.		the following tests been per- ed on the aggregate?		-	
	(a)	Grading and Fineness Modulus (ASTM C136 or ASTM C330)			
	(p)	Amount of Material Finer Than No. 200 Sieve (ASTM Cl17)			
	(c)	Organic Impurities (ASTM C40)		·*****	
	(d)	Mortar Strength Test (ASTM C87)			
	(e)	Soundness (ASTM C88)	-		
	(f)	Friable Particles (ASTM C142)			
	(g)	Coal and Lignite (ASTM C123)			
	(h)	Abrasion of Coarse Aggregate (ASTM Cl31 or ASTM C535)			
	(i)	Specific Gravity and Absorp- tion - Coarse Aggregate (ASTM Cl27)			
	(j)	Specific Gravity and Absorp- tion - Fine Aggregate (ASTM C128)			
	(k)	Bulk Unit Weight (ASTM C29)			
	(1)	Water Soluble Chlorides (ASTM D1411)			
	(m)	Flat or Elongated Particles (ASTM C125 and ASTM D3398 or Corps of Engineers Spec. CRD-C119-53)			

4.2 Aggregates (Continued)

		CHECK LIST	INITIALS	DATE	NOTES
	(n)	Soft Particles (ASTM C235)	-		
	(0)	Compressive and Flexural Strength in Concrete (ASTM C39 and ASTM C78).			
	(p)	Freezing and Thawing Resistance (ASTM C682 or C666)			
	(p)	Reactive Aggregates (ASTM C227, ASTM C289, ASTM C342, and ASTM C586)		-	
4.	test cert	incoming aggreyates sampled and ed to verify supplier's ification and are tests pro- y documented?	***		
5.	gate	procedures for unloading aggre- es prevent harmful segregation breakage?			
6.	prev	procedures for stockpiling ent harmful segration breakage?			
7.	to p incl the	coregate stored in a manner revent contamination and usion of foreign material in concrete, and to insure that egates are not intermingled?			
8.		ree water in aggregates wed to drain prior to their			
٥.	ligh thor	procedures for prewetting atweight aggregate provide cough and uniform distribution water?			
10.	they that are	warine aggregates are used, are washed with fresh water so chloride and sulfate contents within limits of construction cifications?			

4.2 Aggregates (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
11.	Does maximum aggregate size conform to construction specifications?			
12.	Are records available for all above items?			

4.3 Mixing Water

	CHECK LIST	INITIALS	DATE	NOTES
1.	Is water supply adequate and sup- plied at pressures sufficiently uniform to insure accurate measurement?			
				•
2.	Is water potable?			*
3.	Have the following tests been per- formed on the water (including ice) by the Testing Laboratory?			
	(a) Chloride Content (ASTM D512)			
	(b) Sulfate Content (ASTM D516)	*************		
4.	Are chloride and sulfate contents within limits of construction specifications?			
5.	Are records available on all above items?			

4.4 Admixtures

	CHECK LIST	INITIALS	DATE	NOTES
1.	Is handling and storage system adequate to prevent inadvertent mixing or contamination of admixtures?			
2.	Are admixture containers clearly labeled by type, proprietary name, and amount?		-	
3.	Are liquid admixtures protected to prevent freezing?	-		
4.	Is agitation provided for liquid admixtures that are not stable solutions?	-	no disease prince fills	
5.	Are all admixtures being used as specified in construction specifications or as approved by the design office?			
6.	Does air-entraining admixture con- form to ASTM C260?		~~~	
7.	Do water-reducing admixtures, retarding admixtures, accelerating admixtures, water-reducing and retarding admixtures, and water-reducing and accelerating admixtures conform to ASTM C494?		Market State of The State of Th	
8	If pozzolans are used, do they con- form to ASTM C618 and have they been tested for sulfate resistance and corrosion when used in concrete with the selected type of cement?	~~~		
9.	If two or more admixtures are used, is their compatibility documented?	agis supremientos, que		
10.	Does use of admixtures containing chloride ions result in excess chloride content as established by construction specifications?			
11.	Are records available on all above items?			

4.5 Reinforcing and Prestressing Steel

	CHECK LIST	INITIALS	DATE	NOTES
1.	Is deformed steel being used for all reinforcement except spirals or prestressing tendons?		***************************************	
2.	Do deformed reinforcing bars conform to ASTM A615, A616, A617, or A706?			
3.	Are certified test reports of heat number, chemical analysis, and mechanical properties submitted for each heat and size of bar?			
4.	Does yield strength of deformed re- inforcement conform to that deter- mined by tests on full size bars?	***************************************		
5.	Do bend test requirements for deformed reinforcement conform to ACI 318-77, Section 3.5.3.2?			
6.	Is weldable reinforcing steel being used in the splash zone, unless otherwise indicated in the construction specifications?	-		
7.	Do epoxy coated or galvanized rein- forcing bars meet requirements of construction specifications?			
8.	Do bar and rod mats for concrete reinforcement conform to ASTM A184?	-		
9.	Does smooth wire for spiral rein- forcement conform to ASTM A82?			
10.	Does deformed wire for concrete reinforcement conform to ASTM A496?		·	
11.	Does welded smooth wire fabric for concrete reinforcement conform to ASTM A195?			
12.	Does welded deformed wire fabric for concrete reinforcement conform to ASTM A497?		-	

4.5 Reinforcing and Prestressing Steel (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
13.	For bars, wire, or wire fabric with a specified yield strength exceeding 60,000 psi, is the yield strength defined at a stress corresponding to a strain of 0.35 percent?			
14.	Are certified test reports of chemical analysis and mechanical properties submitted for deformed wire, wire fabric, and smooth wire reinforcement?			
15.	Are shipments of reinforcing materials identified as to heat number, manufacturer, size, type, and grade?	**************************************		
16.	Are reinforcing materials segregated and stored according to type, grade, and size?	The improper parties of		
17.	Does the Test Laboratory perform sampling to verify supplier's certifications?			
18.	Is rejected reinforcement tagged and separated from acceptable reinforcement?			
19.	Do prestressing wires, strands, and bars conform to ASTM A421, ASTM A416, and ASTM A722, respectively?	operation and	***************************************	
20.	If low-relaxation wire or strand is specified, are tests in accordance with ASTM E328?			
21.	Do anchorage components for pre- stressing systems conform to dimen- sions, finish, alignment, and tolerances given in Construction Specifications?			

4.5 Reinforcing and Prestressing Steel (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
22.	Are anchorages and couplings capable of developing at least 95% of the minimum specified ultimate tensile strength of the prestressing steel in the unbonded condition without exceeding anticipated set?	-	-	
23.	Have prestressing tendon assemblies been tested under static and dynamic conditions in accordance with PTI Guide Specifications unless otherwise stated in the construction specifications?			
24.	Are certified test reports on pre- stressing materials and tendon assemblies available?			
25.	Are prestressing materials and tendon assemblies shipped and stored in weathertight enclosures to insure protection against corrosion?			
26.	Are welding, flame cutting or similar operations carried out far enough away from stored prestressing tendons to insure that temperature of the tendons is not raised and that tendons are not splashed with weld material?			
27.	Are prestressing tendons kept clean, and free from grease, insoluble oil, deposits of salt, or any other material likely to affect bond or durability?			
28.	Are protective wrappings or coatings for tendons chemically neutral and designed to prevent electro-corrosive attack?			
29.	Are records available for all above items?			

4.6 Post-Tensioning Ducts

	CHECK LIST	INITIALS	DATE	NOTES
1.	Are post-tensioning ducts semi- rigid, mortar-tight, and water- tight with at least 1 mm wall thickness?			
2.	Are ducts nonreactive with concrete, tendons, or filler material?			
3.	Are ferrous ducts or galvanized metal ducts passivated by chromate wash?			
4.	Have plastic ducts been rejected unless specified in construction specifications?			
5.	Do ducts for single wire, strand, or bar tendons have an inside diameter at least 1/4 in. larger than the nominal diameter of the tendon?			
6.	Do ducts for multiple wire, strand, or bar tendons have an inside cross-sectional area at least twice the nominal net area of the enclosed tendon?		-	
7.	Are bell and spigot joints used with saw-cut ends free of burrs and dents?			
8.	Are ducts provided with openings at both ends for grout injection?			
9.	Are ducts stored clear of the ground and protected from weather?			

4.7 Grout for Bonded Tendons

CHECK LIST		INITIALS	DATE	NOTES
1.	Does cement for grout conform to ASTM C150 Type I, II, or III?	Market and Adjustices		
2.	Does dement satisfy limits for tricalcium aluminate content specified in construction specifications?			
3.	Does mixing water satisfy limits on chloride and sulfate content specified in construction specifications?			
4.	Is mixing water potable?			
5.	Does sand, if used, conform to ASTM C144 (with exception of gradation which may be modified as necessary for workability)?			
6.	Have admixtures for grout been tested for possible injurious effects on grout, steel, or concrete (chlorides, for example)?	manak (magana		
7.	Have admixtures been screened to insure that calcium chloride is not used?			
8.	Have mix proportions for grout been established by test results on fresh and hardened material or, alternatively, on the basis of prior documented experience?			
9.	Are total chlorides in grout limited to those stated in construction specifications?	-		
10.	Does water-cement ratio of the grout exceed 0.45 by weight?			
11.	Is free volumetric expansion of grout limited to 10%?			

4.7 Grout for Bonded Tendons (Continued)

	CHECK MIST	INITIALS	DATE	NUTES
12.	Is bleeding of grout, tested in accordance with PTI Guide Specifications, limited to 2% by volume three hours after mixing, and is the separated water reabsorbed after 24 hours?			

4.8 Inserts and Embedments

	CHECK LIST	INITIALS	DATE	NOTES
1.	Is use of aluminum inserts and embedments prohibited?			
2.	Are reinforcing bars used for anchorage of embedment plates made of weldable steel?			
3.	Are reinforcing bars attached to anchorage plates by full penetra- tion welds made in accordance with AWS D12.1?			

4.9 Concrete

	CHECK LIST	INITIALS	DATE	NOTES
*1.	Does the maximum water-cement ratio of the mix conform to the construction specifications?			
*2.	Does the minimum cement content conform to the construction specifications?			
*3.	Does the minimum design compressive strength conform to the construction specifications?			
*4.	Has the minimum design compressive strength been increased, and are aggregates sufficiently hard, in areas where severe abrasion is anticipated?			
*5.	Does amount of air entrainment conform to the construction specifications?	-		
* 6.	Does total chloride content of concrete conform to the construction specifications?	-		
7.	Have measures been established to minimize cracking in thin sections and to prevent excessive thermal stresses in mass concrete where high cement contents (in excess of approximately 700 lbs per cubic yard of concrete) are used?			

5. BATCHING AND MIXING CONCRETE

CHECK LIST		INITIALS	DATE	NOTES
1.	Does the ready mix concrete production facility meet certification requirements established by NRMCA?	Standing of Tanks of Tanks		
2.	Does the accuracy of weighing scales conform to ASTM C94 unless otherwise stated in the construction specifications?			
3,	Are scales arranged so that the plant operator can observe all dials or indicators during the operation?			
4,	Are cement, aggregate, and water weight recorders functioning properly?	-		
5.	Is equipment for automatic measuring of moisture content of aggregate functioning properly?			
6.	Is bulk cement weighed on a separate scale in a separate weigh batcher?	-	****	
7.	Are batching controls inter-locked to prevent starting of a new batching cycle before all batchers are completely empty?			
8.	Is batching equipment capable of meeting accuracy limits stated in ASTM C94?			
9.	Is there leakage when valves are closed in the delivery water system?			
10.	Are filling and discharge valves interlocked to prevent discharging before completion of filling operation?			
11.	Are scale calibration records available?		NET IN COMMENTS	
12.	Are scale calibrations repeated at least quarterly unless otherwise stated in construction specifications?			

5. BATCHING AND MIXING CONCRETE (Continued)

CHECK LIST		INITIALS	DATE	NOTES
13.	If separate dispensers are not used for liquid admixtures, are provisions made for cleaning dispensers when admixtures are changed?			
14.	Is admixture dispenser system free of leaks and properly valved to prevent backflow or siphoning?			
15.	Do mixer and agitator trucks carry TMMB rating plate?			
16.	Do concrete delivery trucks conform to ASTM C94?	-		
17.	Are all trucks equipped with accurate revolution counters?			
18.	Are mixers operated at manu- facturer's designated drum speed?			
19.	When truck mixing, do number of revolutions conform to ASTM C94 or the construction specifications?	-		
20.	Are mixer drums free of hardened concrete?			
21.	When a mixer produces unsatisfactory results, is its use discontinued?			
22.	When ice is used to cool mixing water, is it finely crushed, shaved or chipped?			
23.	Is ice completely melted at end of mixing?			
24.	In cold weather, are provisions made for heating water and/or aggregates to insure specified temperature at placement of concrete?			

5. BATCHING AND MIXING CONCRETE (Continued)

		CHECK LIST	INITIALS	DATE	NOTES
25.	esta is r mixt	cold weather, are procedures ablished to insure that cement not mixed with water, or with cures of water and aggregates, ing a temperature greater than '?			
26.	prov cont snow	cold weather, are there adequate visions to prevent materials taining frozen clumps, ice or from entering batching pment?			
27.	that are	precautions taken to insure deleterious salts or chemicals not used to lower the freezing at of water?			
28.	for in a	batching and mixing procedures lightweight aggregate concrete accordance with the construction ifications?			
*29.		delivery tickets contain fol- ing information:			
	(a)	Name of ready-mixed concrete company?			
	(b)	Plant designation where batched?			
	(c)	Ticket serial number?			
	(đ)	Truck number or designation?			
	(e)	Name of contractor or purchaser?	حودستين		
	(f)	Job designation?			
	(g)	Concrete designation?			
	(h)	Amount of concrete (cubic yards)?			
	(i)	Date?			
	(j)	Time batch was loaded?			

5. BATCHING AND MIXING CONCRETE (Continued)

		CHECK LIST	INITIALS	DATE	<u>NOTES</u>
	(k)	Extra water added at request of receiver and his signature?			
	(1)	Type and name of admixtures and emount batched?			
*30.		delivery tickets properly ed in and signed?			
*31.		elivery tickets accompany each of concrete?	Phasel-part again		
*32.		delivery tickets completed and dat point of receipt?			

6.1 Reinforcement

	CHECK LIST	INITIALS	DATE	NOTES
*1.	At time of concrete placement, is reinforcement free of mud, loose rust, grease, oil, deposits of salts, ice, snow, or other materials that may adversely affect bond or durability?			
*2.	Do reinforcing bars with mill-scale or rust meet minimum dimensions specified in ASTM A615, A616, A617, or A706 as applicable (based on hand wire brushed test specimen)?			
*3.	Where standard hooks for reinforcing bars are specified, do they conform to ACI 318?		•	
*4.	Do bend diameters of reinforcement conform to ACI 318, unless otherwise stated in the construction specifications?			
5.	Is reinforcement fabricated prior to placement cold bent?			
6.	Are provisions made to insure that field bending of reinforcement partially embedded in concrete is only done after approval by the project engineer, unless such bends are shown on construction drawings?			
7.	Do welds of reinforcing bars conform to AWS D12.1?			
8.	Are welders qualified in accordance with AWS Dl2.1?			
*9.	Are records of welding procedures and weld qualifications maintained?			
*10.	Are procedures established to insure that tack welds are not used on reinforcement unless authorized by the project engineer?			

6.1 Reinforcement (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
11.	Do welding procedures prohibit grounding to reinforcement?			
12.	Is reinforcement protected against weld splatter and arcs due to strikes or current drainage?	***************************************		
*13.	Are completed welds visually inspected for cracks and size?			
*14.	Are defective welds repaired or replaced?			
*15.	Are reinforcing bar splices located in accordance with the construction specifications?			
*16.	Is length of lap splices of rein- forcing bars and welded wire fabric in accordance with the construction specifications?			
*17.	Are anchorage lengths of embedded reinforcement in accordance with the construction specifications?			
*18.	Do mechanical splices of rein- forcement conform to the con- struction specifications?		·	
19.	Have tensile tests conforming to ASTM A370 been conducted on samples of bars mechanically spliced to insure that strength of the bar can be developed and that elongation across the splice does not exceed specified limits?			
*20.	Is reinforcement located and securely supported to insure that specified concrete cover will be obtained?			
*21.	Is reinforcement placed within tolerances specified in ACI 318 unless otherwise stated in the construction specifications?	an of addinguishing		

6.1 Reinforcement (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
*22.	Does spacing of reinforcement conform to ACI 318 unless otherwise stated in the construction specifications?	alan a Propinsi da San Albanda da S		
*23.	Does use of bundled reinforcement conform to requirements of ACI 318 unless otherwise stated in construction specifications?			

6.2 Prestressing Tendons

	CHECK LIST	INITIALS	DATE	NOTES
*1.	Is all steel for prestressing tendons free of mud, rust, grease, insoluble oil, deposits of salt, or any other material that may dversely affect bond or durability?			
2.	Are welding operations conducted to insure that temperature of prestressing steel is not raised and that tendons are not splashed with weld material?			
2	De welding pusedware pushibit			
3.	Do welding procedures prohibit grounding to prestressing tendons?			
*4.	Are ducts for presuressing tendons located in accordance with construction drawings?		-	
*5.	Are tolerances in placement of ducts for prestressing tendons in accordance with ACI 318 unless otherwise stated in the construction specifications?			
* 6.	Are ducts securely fastened to prevent movement during concreting?		•	
* 7.	Are ducts watertight with splices taped to prevent intrusion of water, grout, or concrete?	middles garden		
*8.	Are ends of ducts sealed during construction to prevent entry of water?	-		
9.	If ducts are coated to protect against excessive rust, is a chemically neutral protective agent, such as a vapor phase inhibitor powder, employed?			
10.	Are air vents provided at peaks in the duct profile?			

6.2 Prestressing Tendons (Continued)

be met?

	CHECK LIST	INITIALS	DATE	NOTES
*11.	Are drains provided at valleys of duct profile?	-		
*12.	Are couplers used only in locations specified on construction drawings?		~	
*13.	Are coupler housings long enough to permit necessary movements?		~~~	
*14.	If flexible metal ducts are specified in special areas, are they supported by curved bearing plates to prevent local crushing?		-	
*15.	Are ducts inspected for damage after placement of ducts, reinforcement, embedments, and forming is complete?			
*16.	Are holes or openings repaired prior to concrete placement?			
*17.	Are anchorages (bearing plates) located, aligned, and secured to insure that tolerances in the construction specifications will			

6.3 Formwork and Embedments

	CHECK LIST	INITIALS	DATE	NOTES
*1.	Is formwork located to insure that the final structure will conform to shape, lines, dimensions, and tolerances stated in construction specifications and drawings?			
*2.	Is formwork constructed, supported, and braced in accordance with the construction specifications?			
3.	Is formwork constructed so as not to damage previously placed concrete?			
*4.	Is formwork sufficiently tight to prevent leakage of mortar?	-		
*5.	Are water and foreign matter being removed from interior of forms prior to concrete placement?	***************************************		
* 6.	Is formwork cleaned before reuse?			
* 7.	Has specified release agent been applied to formwork?			
*8.	If precast concrete segments are used as forms, are placement tolerances in conformance with the construction specifications?			
*9.	If precast concrete segments are used as forms, have surfaces been prepared in accordance with construction specifications?			
*10.	Are precast concrete segments sup- ported to prevent movement during concreting?			
* 11.	Are ties and connectors between precast concrete form segments in accordance with construction specifications?			
12.	Are construction loads monitored to insure that formwork is not			

accidentally overloaded?

6.3 Formwork and Embedments (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
*13.	Are embedded items secured in position, inspected and approved prior to concrete placement?	***		
*14.	Are metallic embedded items and anchors electrically isolated from primary steel reinforcement in accordance with construction specifications?			
*15.	Are embedded items free of oil, grease, dirt, paint, rust, deposits of salt, or any other material that may adversely affect bond or durability?	-		
*16.	Are premolded waterstops, if specified, installed to minimize the number of joints?	***************************************		
*17.	Are voids in sleeves, inserts, and anchor slots protected against intrusion of concrete?			

6.4 Construction Joints

	CHECK LIST	INITIALS	DATE	NOTES
*1.	Are construction joints located as indicated in construction specifications and drawings?			
*2.	Are construction joints cleaned in accordance with construction specifications to remove laitance and unsound material, and to uniformly expose coarse aggregate?	-		
*3.	After cleaning, is maximum size aggregate exposed to approximately 25% of its nominal diameter?			
*4.	If specified, is epoxy-resin or other bonding compound applied in accordance with manufacturer's recommendations?			
* 5.	If specified, is cement content being increased at start of the next placement?			
*6.	Are construction joints inspected after forms are placed to insure that form release agents or other foreign materials have not come into contact with the hardened concrete surface against which fresh concrete is to be placed?			

7. INSPECTION DURING CONCRETING

	CHECK LIST	INITIALS	DATE	NOTES
*1.	Are material proportions and admixtures in accordance with approved mix design?			
*2.	Is concrete transported from mixers to place of final deposit by methods that prevent segregation or loss of materials?	-	-	
3.	Is transporting equipment adequate to insure continuous supply of concrete without delays in excess of limits given in the construction specifications?	- Translation by the Control of the	Nagara processor (Free	
4.	If concrete is pumped, have trials been made to insure compatibility of mix with equipment being used?	•	·	
5.	If concrete is pumped, is use of aluminum or aluminum alloy pipe prohibited?	-		
*6.	Is equipment for transporting and placement clean and free of foreign material?		the second	
*7.	Are delivery tickets being com- pleted at point of receipt of concrete?		- William of the Control of the Cont	
*8.	Are batches rejected if they do not meet slump requirements of the construction specifications?			
9.	Is there adequate control to prevent use of concrete that has contained its mixing water for a period longer than stated in the construction specifications?	-		
10.	Is there adequate control to prevent use of concrete that has attained initial set?			

7. INSPECTION DURING CONCRETING (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
11.	Is addition of water and remixing of concrete, if required, done under careful supervision and in accordance with the construction specifications?			
*12.	If ice or foreign materials are present in concrete, is the batch rejected?			
*13.	Are rejected batches noted on delivery ticket?			
*14.	Are required number of control test specimens being made in accordance with the construction specifications?			
*15.	Are placement temperatures of concrete within limits stated in the construction specifications?			
16.	Do the construction specifications permit concrete placement during rain, sleet, or snow?			
17.	Are procedures established to pre- vent rainwater from increasing mixing water or damaging the con- crete surfaces?			
*18.	Is concrete deposited as near as possible to its final location?			
*19.	Is concrete deposited so as to avoid segregation or loss of materials?			
*20.	Is concrete thoroughly consolidated by vibration immediately after placement?			
*21.	Is placement of internal vibrators and spacing of external vibrators adequate to insure complete consolidation?			

7. INSPECTION DURING CONCRETING (Continued)

		CHECK LIST	INITIALS	DATE	NOTES
*22.	arou	oncrete thoroughly worked nd reinforcement and embedded ures, and into corners of s?			
*23.	free blee	there any evidence of excess water, indicating excessive ding, at top of lifts after rete is consolidated?	-		
*24.		the following records being tained:			
	(a)	Delivery batch tickets?			
	(b)	Daily summary report of batch plant activities?			
	(c)	Daily summary report of concrete field operations?			
	(đ)	Records of disposition of rejected batches?			
	(e)	Test results?			
	(f)	Copies of batch plant recorder tapes for each batch?			
*25.		slump tests being performed ccordance with ASTM C143?			
*26.	perf	tests for air content being ormed in accordance with ASTM or ASTM C173 or ASTM C138?			
*27.	conc	nit weight, of normal weight rete being measured in accord- with ASTM Cl38?			
28,	meet unit been weig ASTM unit	lightweight concrete that must specified limits on air-dry weight, has fresh unit weight correlated with air-dry unit ht (tested in accordance with C567) to permit use of fresh weight as basis for ptance?		***************************************	

7. INSPECTION DURING CONCRETING (Continued)

	CHRCR LIST	INITIALS	DATE	NOTES
*29.	Are control test specimens being made and cured in accordance with ASTM C31?			
30.	If concrete is pumped, has a correlation been established for differences in concrete properties sampled at point of delivery to pump and at point of discharge from line?			

8.1 Finishing, Curing, and Formwork Removal

	CHECK LIST	INITIALS	DATE	NOTES
*1.	For decks or other flatwork, after concrete has been placed, consolidated, and screeded; are floating and troweling delayed until the surface water sheen has disappeared?			
*2.	Is freshly placed concrete main- tained in a moist condition for the period stated in the construction specification?			
*3.	Do the construction specifications permit use of a heavy-duty membrane curing compound or a curing mat cover to prevent loss of moisture in lieu of continuous moist curing?			
*4.	Unless specifically permitted by the construction specifications, is seawater prohibited for curing concrete?			
*5.	In cold weather, is minimum temperature of concrete kept above the limit stated in the construction specification?			
6.	In cold weather, are precautions taken to insure that freshly placed concrete is not exposed to carbon dioxide from exhaust gases of heaters?			
* 7.	In hot weather, are procedures established to keep surfaces from cracking due to rapid drying?	angula Proposition		
* 8.	Is concrete damaged by freezing rejected and replaced?			
* 9.	Is concrete damaged by accelerated evaporation rejected and replaced?			

8.1 Finishing, Curing, and Formwork Removal (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
10.	If accelerated curing is used for precast segments, is the curing process documented to insure strength and durability equivalent to standard moist curing?			
11.	Are forms and shores removed only after test strengths of concrete are sufficient to insure that the structure can support its own weight plus any construction loads?			
*12.	Are procedures for formwork removal such that they do not impair safety or serviceability of the structure?			
*13.	After removal of formwork, are formed surfaces finished in accordance with the construction specifications?			
*14.	After removal of formwork, are holes left from form ties filled in accordance with the construction specifications?			
*15.	If defects such as honeycombing occur, is their significance with regard to future performance evaluated prior to undertaking repair?		APPROXIMATION AND ADMINISTRATION AND ADMINISTRATION AND ADMINISTRATION AND ADMINISTRATION AND ADMINISTRATION A	
*16.	If defects such as honeycombing are to be repaired, are repair procedures used in accordance with the construction specifications?			

8.2 Control Tests of Hardened Concrete

	CHECK LIST	INITIALS	DATE	NOTES
1.	Are control test specimens being cured in accordance with ASTM C31?			
2.	Are test cylinders being tested for compressive strength in accordance with ASTM C39?			
3.	Are required numbers of control specimens being tested in accordance with construction specification?			
4.	Are test specimens being weighed?			
5.	Does structural lighweight con- crete meet specified limit on air-dry unit weight as tested in accordance with ASTM C567?			
6.	Are results of control tests properly documented?		-	
7.	If splitting tensile tests are required by the construction specification, are tests being conducted in accordance with ASTM C4967			
8.	Is evaluation of strength test results in accordance with the construction specification?			

8.3 Post-Tensioning and Grouting

	CHECK LIST	INITIALS	DATE	NOTES
1.	Are post-tensioning operations under direction of an experienced supervisor and carried out by trained operators?			
*2.	Are tendons being stressed in sequence stated in construction specification?		***************************************	
*3.	Has concrete reached specified strength prior to start of post-tensioning?	-	***************************************	
*4.	Are components of tensioning equip- ment accurately set, aligned, and securely supported prior to start of tensioning?			
* 5.	Are post-tensioning forces deter- mined by measurement of tendon elongation and by measurement of jacking force?			
*6.	Is the cause for any difference of more than 5% between the two methods of measurement of post-tensioning forces determined and corrected?	-	· Samuel and Samuel an	
* 7.	Is the total loss of prestress resulting from unreplaced broken tendon elements less than 2% of the total prestress?		***************************************	
8.	Are hydraulic pressure gages for measuring jacking force calibrated against known standards (the gage and jack should be calibrated as a unit)?			
9.	If load cells are used for measuring jacking force, are they calibrated against known standards?			
10.	Are maximum stressing force levels in conformance with the construction specification?		*****	

8.3 Post-Tensioning and Grouting (Continued)

	CHECK LIST	INITIALS	ATE	NOTES
*11.	Are records kept for all stressing operations?		•	
*12.	If precast segmental construction is used, are procedures for treat-ment of surfaces between segments in accordance with the construction specifications?			
13.	Is grout for permanent protection of post-tensioning tendons mixed in equipment capable of continuous mechanical mixing and agitation that will produce uniform distribution of materials?			
14.	Are procedures established to insure that water is not added to increase grout flowability that has been decreased by delayed use of grout?			
15.	Is the grout screened prior to its introduction into the pump?			
16.	Is the grout pumped continuously to prevent air from being drawn into the post-tensioning duct?	and the second second		
*17.	Are grout temperatures limited to less than 90F during mixing and pumping?			
*18.	Has all oil or similar material used for internal protection of the duct been removed prior to grouting (water-soluble oil may be left in ducts or on tendons)?			
19.	Are procedures for opening and closing air vents and drains established prior to start of grouting?			
20.	Is pumping pressure at tendon inlet limited to maximum specified?			

8.3 Post-Tensioning and Grouting (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
21.	Do procedures for grouting long vertical tendons insure that no water is trapped at the upper end because of bleeding or other causes?			
22.	Have procedures been established, or are thixotropic admixtures being used, to prevent pockets caused by bleeding when grouting vertical or steeply inclined tendons?	·	**************************************	
*23.	In cold weather, is grout protected from freezing?			
*24.	Are prestressing anchorages pro- tected from exposure to seawater in accordance with the construc- tion specification?	-		

9. IN-SERVICE INSPECTION

	CHECK LIST	INITIALS	DATE	NOTES
1.	Has vessel been surveyed within required inspection period?			
2.	Have records from previous in-service inspection surveys been reviewed?			
3.	Has a reference system been estab- lished to permit clear identifica- tion of inspected areas and to permit accurate designation of location of problem areas?			
4.	Are data sheets and forms available for recording results of in-service condition inspection?	***************************************	, 	
5.	Has marine growth or other debris been removed as required to permit inspections?	Nad Miller and a		
5.	With regard to damage, have exterior and interior of vessel been visually inspected for signs of:			
	(a) Impact damage?	-		
	(b) Excessive distortions?			
	<pre>(c) Flexural cracking (hogging or sagging)?</pre>			
	(d) Torsional cracking?			
	(e) Shear cracking?	-		
	(f) Concrete crushing?			
7.	With regard to durability, have exterior and interior of vessel been visually inspected for signs of:			
	(a) Cracking?	···	·	
	(b) Spalling?			
	(c) Scaling?			
	(d) Disintegration?			

9. IN-SERVICE INSPECTION (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
	(e) Popouts?			
	(f) Erosion?	The company of the little of t		
	(g) Corrosion?			
	(h) Water Leakage?		·····	
8.	Have areas around prestressing tendons anchorages been inspected for signs of corrosion or deterioration?			
9.	Have cathodic protection systems, if used, been inspected and serviced?			
10.	Have exposed metal components and embedments been inspected for corrosion or other signs of deterioration?			
11.	Have areas previously repaired been closely inspected to evaluate condition of repair?			
12.	Has condition of protective coatings, if used, been inspected?	-		
13.	Feed following parts of the vessel been given special attention:			
	(a) Areas subjected to alternate wetting and drying?			
	(b) Areas subjected to freezing and thawing?	-	Management of the second	
	(c) Areas - stress concentrations?			
	(d) Area, of critical load transfer?			
	(e) Areas containing construction joints?			
	(f) Areas ~ _ously repaired?		***************************************	

9. IN-BERVICE INSPECTION (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
14.	Are divers selected for underwater inspection qualified, experienced, trained for examination of concrete hulls, and adequately briefed on the project?			
15.	Are areas that require detailed examination and nondestructive testing clearly marked?			
	•			
16.	If areas of deterioration are suspected of affecting structural integrity of the vessel, are proce- dures for engineering review prior to repairs being undertaken?			
	CO TENETTE DETIN MINET CAVAIII			

10. IN SITU TESTING OF HARDENED CONCRETE

	CHECK LIST	INITIALS	DATE	NOTES
1.	Have specifications for test methods and sampling plan been appraised by USCG?		Wasawa T	
2.	Is hardened concrete being examined and sampled following practices recommended in ASTM C823?		**************************************	
3.	For evaluation of hardened concrete under water, have accuracy and reliability of test method selected been documented?			
4.	If drilled cores and sawed beams are specified for evaluating hardened concrete, are they obtained and tested in accordance with ASTM C42?			
5.	Are numbers and locations of cores and beams obtained in accordance with specifications?			
6.	Are test data on cores and beams available to correlate results for differences in moisture content between samples as tested and in situ concrete?			
7.	Are holes left from drilled cores and sawed beams filled in accordance with specified repair procedures?	-		
8.	Are records available for core and beam test results?			
9.	If a rebound hammer is being used to evaluate hardened concrete, are rebound numbers obtained in accord- ance with ASTM C805?		-	
10.	If specified, has rebound hammer been calibrated using concrete cylinders made from same concrete as in the vessel?		•••	
11.	If specified, are data available to correlate rebound numbers with core tests?			

10 IN SITU TESTING OF HARDENED CONCRETE (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
12.	If rebound numbers are correlated with core tests, are differences in moisture conditions considered?			
13.	Are numbers and locations of rebound readings in accordance with specifications?	ang and throughter		
14.	Are records available for rebound hammer test results?			
15.	If a penetration device is being used to evaluate hardened concrete, is penetration resistance obtained in accordance with ASTM C803?			
16,	Are numbers and locations of pene- tration readings in accordance with specifications?	منجيوبون		
17.	If specified, has penetration device been calibrated using concrete made with same materials?			
18.	Are holes left from penetration tests filled in accordance with specified repair procedures?			
19.	Are records available for penetra- tion test results?			
20.	If pullout tests are specified for evaluating hardened concrete, are pullout strengths obtained in accordance with ASTM C900?	-		
21.	Are numbers and locations of pullout inserts in accordance with specifications (Note: Some pullout test methods must be planned prior to construction because inserts must be embedded in fresh concrete.)?	-		
22.	Has pullout strength been correlated with compressive strength?			
23.	Are holes left from pullout tests filled in accordance with specified repair procedures?		,	

10. IN SITU TESTING OF HARDENED CONCRETE (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
24.	Are records available for pullout test results?	-	and the second second	
25.	If ultrasonic pulse velocity methods are specified for evaluating hardened concrete, are pulse velocities obtained in accordance with ASTM C597?	******		
26.	Are numbers and locations of pulse velocity measurements in accordance with specifications?			
27.	Are records available for pulse velocity test results?			
28.	If specified for evaluating corrosion activity of reinforcing steel in concrete, are tests of half cell potentials conducted in accordance with ASTM C876?			
29.	Are numbers and locations of half cell potential measurements in accordance with specifications?			
30.	Are records available for half cell potential test results?			
31.	If specified for evaluating deteriorated concrete, are petrographic examinations of hardened concrete in accordance with practices recommended in ASTM C856?			
32.	Where applicable, are physical and chemical tests made to support petrographic examinations conducted in accordance with relevant ASTM Standards?			
33.	Are records available for results of petrographic examinations and supplementary physical and chemical tests?			
34.	If nonstandard tests are required, are they made in accordance with procedures that have been approved by the USCG?			

10. IN SITU TESTING OF HARDENED CONCRETE (Continued)

CHECK LIST

INITIALS DATE NOTES

35. If load tests are considered necessary to confirm safety of the vessel, are they conducted in accordance with procedures approved by the USCG?

11. REPAIRS

	CHECK LIST	INITIALS	DATE	NOTES
1.	Has cause of defect been determined and have remedial measures been established to prevent recurrence?			
2.	Have plans and specifications for structural repairs been approved by the USCG?			
3.	Has a conference been held with USCG, Owner, ABS, Contractor, Testing Laboratory, and other interested parties to review structural repair specifications prior to start of operations?			
4.	Have plans and specifications for repairs been reviewed by inspector prior to start of repair operations?		-	
5.	Have provisions been made for docu- mentation of repair operations?		-	
6.	Has consideration been given to insuring that the repair method selected will not adversely affect future durability of the vessel?			
7.	Have repair procedures selected been proved and documented by prior use or by tests under conditions similar to those in the vessel to be repaired?			
8.	Unless otherwise specified, do cement, water, aggregates, and admixtures used for repair meet materials specifications required for new construction?			
9.	Unless otherwise specified, do reinforcing materials used for repair meet materials specifications required for new construction?			
10.	Do procedures for welding rein- forcement during repairs conform to AWS D12.1?			

11. REPAIRS (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
11.	If repairs are made using lap or mechanical splices of reinforce-ment, are splices located and made in accordance with repair specifications?			
12.	Do mortar, concrete, or other repair materials have strengths, deforma- tion characteristics, and thermal expansion characteristics that are compatible with the original concrete?			
13.	As required by the particular repair condition, are organic resins or latex repair materials effective in damp, wet, and cold environments?			
14.	Are organic resins or latex repair materials suitable for application to damp concrete under environmental conditions dictated by job requirements?			
15.	Are manufacturer's instructions for application of repair materials strictly followed unless otherwise specified?			
16.	Prior to application of repair materials, is all unsound, loose and foreign material removed?			
17.	Prior to application of repair materials, is defective or deteriorated concrete completely removed to expose sound uncontaminated concrete?			
18.	Is special consideration given to insure removal of all concrete that shows evidence of active or potential corrosion?		•	
19.	Prior to application of repair materials, is exposed reinforcement thoroughly cleaned?			

11. REPAIRS (Continued)

	CHECK LIST	INITIALS	DATE	NOTES
20.	Are surfaces against which repair materials are to be applied free of grease, oil, or other contaminants that may affect bond?			
21.	Are cracks to be repaired free of dust, oil, disintegrated material, and any debris that could affect intrusion and bond of the repair material?			
22.	If cracks are repaired by epoxy injection, are procedures being used in accordance with repair specifications?			
23.	For repairs using portland cement concrete, mortar, grout, or shot-crete, are curing procedures in accordance with repair specifications?		Angelin majerina	
24.	Are procedures established for inspection and qualty control of underwater repairs?			
25.	Are procedures established to insure safe storage and handling of volatile, flammable, or potentially toxic repair materials?			
26.	Are all repair operations documented and recorded?			

ASTM DESIGNATION	TITLE
A82	Standard Specification for Cold-Drawn Steel Wire for Con- crete Reinforcement
A184	Standard Specification for Fabricated Deformed Steel Bar Mats for Concrete Reinforcement
A185	Standard Specification for Welded Steel Wire Fabric for Concrete Reinforcement
A370	Standard Methods and Definitions for Mechanical Testing of Steel Products
A416	Standard Specification for Uncoated Seven-Wire Stress- Relieved Strand for Prestressed Concrete
A421	Standard Specification for Uncoated Stress-Relieved Wire for Prestressed Concrete
A496	Standard Specification for Deformed Steel Wire for Concrete Reinforcement
A497	Standard Specification for Welded Deformed Steel Wire Fabric for Concrete Reinforcement
A615	Standard Specification for Deformed and Plain Billet-Steel Bars for Concrete Reinforcement
A616	Standard Specification for Rail-Steel Deformed and Plain Bars for Concrete Reinforcement
A617	Standard Specification for Axle-Steel Deformed and Plain Bars for Concrete Reinforcement
A704	Standard Specification for Welded Steel Plain Bar or Rod Mats for Concrete Reinforcement
A706	Standard Specification for Low-Alloy Steel Deformed Bars for Concrete Reinforcement

⁽¹⁾ American Society for Testing and Materials (ASTM), 1916 Race Street, Philadelphia, PA 19103

⁽²⁾ Use latest edition

ASTM DESIGNATION	TITLE
A722	Standard Specification for Uncoated High-Strength Steel Bar for Prestressing Concrete
A767	Standard Specification for Zinc-Coated (Galvanized) Bars for Concrete Reinforcement

ASTM DESIGNATION

TITLE

E328

Recommended Practice for Stress-Relaxation Tests for Materials and Structures

⁽¹⁾ American Society for Testing and Materials (ASTM), 1916 Race Street, Philadelphia, PA 19103

⁽²⁾ Use latest edition

APPENDIX A - APPLICABLE ASIM STANDARDS (1) Annual Book of ASIM Standards - Part 13

ASTM DESTGNATION	TITLE
C109	Standard Test Method for Compressive Strength of Hydraulic Cement Mortars (Using 2-in, or 50-mm Cube Specimens)
C114	Standard Methods for Chemical Analysis of Hydraulic Cement
C115	Standard Test Method for Fineness of Portland Cement by the Turbidimeter
C150	Standard Specification for Portland Cement
C151	Standard Test Method for Autoclave Expansion of Portland Cement
C157	Standard Test Method for Length Change of Hardened Cement Mortar and Concrete
C183	Standard Methods of Sampling Hydraulic Cement
C185	Standard Test Method for Air Content of Hydraulic Cement Mortar
C186	Standard Test Method for Heat of Hydration of Hydraulic Cement
C187	Standard Test Method for Normal Consistency of Hydraulic Cement
C188	Standard Test Method for Density of Hydraulic Cement
C190	Standard Test Method for Tensile Strength of Hydraulic Cement Mortars
C191	Standard Test Method for Time of Setting of Hydraulic Cement by Vicat Needle
C204	Standard Test Method for Fineness of Portland Cement by Air Permeability Apparatus
C219	Standard Definitions of Terms Relating to Hydraulic Coment
C265	Standard Test Method for Calcium Sulfate in Hydrated Portland Cement Mortar

⁽¹⁾ American Society for Testing and Materials (ASTM), 1916 Race Street, Philadelphia, PA 19103

⁽²⁾ Use latest edition

ASTM DESIGNATION	TITLE
C266	Standard Test Method for Time of Setting of Kydraulic Cement by Gillmore Needles
C305	Standard Method for Mechanical Mixing of Hydraulic Cement Pastes and Mortars of Plastic Consistency
C348	Standard Test Method for Flexural Strength of Hydraulic Cement Mortars
C349	Standard Test Method for Compressive Strength of Hydraulic Cement Mortars (Using Portions of Prisms Broken in Flexure)
C451	Standard Test Method for Early Stiffening of Portland Cement (Paste Method)
C452	Standard Test Method for Potential Expansion of Portland Cement Mortars Exposed to Sulfate
C490	Standard Specification for Apparatus for Use in Measurment of Length Change of Hardened Cement Paste, Mortar, and Concrete
C511	Standard Specification for Moist Cabinets, Moist Rooms, and Water Storage Tanks Used in the Testing of Hydraulic Cements and Concretes
C595	Standard Specification for Blended Hydraulic Cements
C596	Standard Method of Measuring the Drying Shrinkage of Mortar Containing Portland Cement

APPENDIX A - APPLICABLE ASTM STANDARDS (1) Annual Book of ASTM Standards - Part 14

ASTM DESIGNATION	TITLE
C29	Standard Test Method for Unit Weight and Voids in Aggregate
C31	Standard Method of Making and Curing Concrete Test Specimens in the Field
C33	Standard Specification for Concrete Aggregates
C39	Standard Test Method for Compressive Strength of Cylindrical Concrete Specimens
C40	Standard Test Method for Organic Impurities in Sands for Concrete
C42	Standard Method of Obtaining and Testing Drilled Cores and Sawed Beams of Concrete
C70	Standard Test Method for Surface Moisture in Fine Aggregate
C78	Standard Test Method for Flexural Strength of Concrete (Using Simple Beam with Third-Point Loading)
C87	Standard Test Method for Effect of Organic Impurities in Fine Aggregate on Strength of Mortar
C88	Standard Test Methodfor Soundness of Aggregates by Use of Sodium Sulfate or Magnesium Sulfate
C94	Standard Specification for Ready-Mixed Concrete
C116	Standard Test Method for Compressive Strength of Concrete Using Portions of Beams Broken in Flexure
C117	Standard Test Method for Materials Finer than No. 200 (75-µm) Sieve in Mineral Aggregates by Washing
C123	Standard Test Method for Lightweight Pieces in Aggregate
C125	Standard Definitions of Terms Relating to Concrete and Concrete Aggregates
C127	Standard Test Method for Specific Gravity and Absorption of Coarse Aggregate
C128	Standard Test Method for Specific Gravity and Absorption of Fine Aggregate

⁽¹⁾ American Society for Testing and Materials (ASTM), 1916 Race Street, Philadelphia, PA 19103

⁽²⁾ Use latest edition

ASTM DESIGNATION	TITLE
C131	Standard Test Method for Resistance to Abrasion of Small Size Coarse Aggregate by Use of the Los Angeles Machine
C136	Standard Test Method for Sieve or Screen Analysis of Fine and Coarse Aggregates
C138	Standard Test Method for Unit Weight, Yield, and Air Content (Gravimetric) of Concrete
C142	Standard Test Method for Clay Lumps and Friable Particles in Aggregates
C143	Standard Test Method for Slump of Portland Cement Concrete
C144	Standard Specifications for Aggregate for Masonry Mortar
C156	Standard Test Method for Water Retention by Concrete Curing Materials
C171	Standard Specification for Sheet Materials for Curing Concrete
C172	Standard Method of Sampling Fresh Concrete
C173	Standard Test Method for Air Content of Freshly Mixed Concrete by the Volumetric Method
C174	Standard Method of Measuring Length of Drilled Concrete Cores
C192	Standard Method of Making and Curing Concrete Test Specimens in the Laboratory
C215	Standard Test Method for Fundamental Transverse, Longitudinal, and Torsional Frequencies of Concrete Specimens
C227	Standard Test Method for Potential Alkali Reactivity of Cement - Aggregate Combinations (Mortar-Bar Method)
C230	Standard Specification for Flow Table for Use in Tests of Hydraulic Cement
C231	Standard Test Method for Air Content of Freshly Mixed Concrete by the Pressure Method
C2 32	Standard Test Method for Bleeding of Concrete
C233	Standard Method of Testing Air-Entraining Admixtures for Concrete

ASTM DESIGNATION	TITLE
C235	Standard Test Method for Scratch Hardness of Coarse Aggregate Particles
C260	Standard Specification for Air-Entraining Admixtures for Concrete
C289	Standard Test Method for Potential Reactivity of Aggregates (Chemical Method)
C293	Standard Test Method for Flexural Strength of Concrete (Using Simple Beam with Center-Point Loading)
C294	Standard Descriptive Nomenclature of Constituents of Natural Mineral Aggregates
C295	Standard Recommended Practice for Petrographic Examination of Aggregates for Concrete
C309	Standard Specification for Liquid Membrane-Forming Com- pounds for Curing Concrete
C311	Standard Methods of Sampling and Testing Fly Ash or Natural Pozzolans for Use as a Mineral Admixture in Portland Cement Concrete
C330	Standard Specification for Lightweight Aggregates for Structural Concrete
C341	Standard Test Method for Length Change of Drilled or Sawed Specimens of Cement Mortar and Concrete
C342	Standard Test Method for Potential Volume Change of Cement-Aggregate Combinations
C387	Standard Specification for Packaged, Dry, Combined Materials for Mortar and Concrete
C403	Standard Test Method for Time of Setting of Concrete Mixtures by Penetration Resistance
C418	Standard Test Method for Abrasion Resistance of Concrete by Sandblasting
C441	Standard Test Method for Effectiveness of Mineral Admixtures in Preventing Excessive Expansion of Concrete Due to the Alkali-Aggregate Reaction

ASTM DESIGNATION	TITLE
C457	Standard Recommended Practice for Microscopical Determination of Air-Void Content and Parameters of the Air-Void System in Hardened Concrete
C469	Standard Test Method for Static Modulus of Elasticity and Poisson's Ratio of Concrete in Compression
C470	Standard Specification for Molds for Forming Concrete Test Cylinders Vertically
C494	Standard Specification for Chemical Admixtures for Concrete
C496	Standard Test Method for Splitting Tensile Strength of Cylindrical Concrete Specimens
C512	Standard Test Method for Creep of Concrete in Compression
C535	Standard Test Method for Resistance to Abrasion of Large Size Coarse Aggregate by Use of the Los Angeles Machine
C566	Standard Test Method for Total Moisture Content of Aggregate by Drying
C567	Standard Test Method for Unit Weight of Structural Light-Weight Concrete
C586	Standard Test Method for Potential Alkali Reactivity of Carbonate Rocks for Concrete Aggregates (Rock Cylinder Method)
C597	Standard Test Method for Pulse Velocity Through Concrete
C617	Standard Method of Capping Cvlindrical Concrete Specimens
C618	Standard Specification for Fly Ash and Raw or Calcined Natural Pozzolan for Use as a Mineral Admixture in Portland Cement Concrete
C642	Standard Test Method for Specific Gravity, Absorption, and Voids in Hardened Concrete
C656	Standard Test Method for Resistance of Concrete to Rapid Freezing and Thawing
C671	Standard Test Method for Critical Dilation of Concrete Specimens Subjected to Freezing
C672	Standard Test Method for Scaling Resistance of Concrete Surfaces Exposed to Defeing Chemicals

ASTM DESIGNATION	TITLE
C682	Standard Recommended Practice for Evaluation of Frost Resistance of Coarse Aggregates in Air-Entrained Concrete by Critical Dilation Procedures
C683	Standard Test Method for Compressive and Flexural Strength of Concrete Under Field Conditions
C684	Standard Method of Making, Accelerated Curing, and Testing of Concrete Compression Test Specimens
C685	Standard Specification for Concrete Made by Volumetric Batching and Continuous Mixing
C702	Standard Methods for Reducing Field Samples of Aggregate to Testing Size
C803	Tenative Test Method for Penetration Resistance of Hardened Concrete
C805	Standard Test Method for Rebound Number of Hardened Concrete
C823	Standard Recommended Practice for Examination and Sampling of Hardened Concrete in Constructions
C827	Standard Test Method for Early Volume Change of Cementitious Mixtures
C851	Standard Recommended Practice for Estimating Scratch Hard- ness of Coarse Aggregate Particles
C856	Standard Recommended Practice for Petrographic Examination of Hardened Concrete
C873	Tentative Test Method for Compressive Strength of Concrete Cylinders Cast in Place in Cylindrical Molds
C876	Standard Test Method for Half Cell Potentials of Reinforcing Steel in Concrete
C881	Standard Specification for Epoxy-Resin-Base Bonding Systems for Concrete
C882	Standard Test Method for Bond Strength of Epoxy-Rosin Systems Used With Concrete
C883	Standard Test Method for Effective Shrinkage of Epoxy-Resin Systems Used With Concrete

ASTM DESTGNATION	ŢŢŢĻĸ
C884	Standard Test Method for Thermal Compatibility Between Concrete and An Apoxy-Resin Overlay
C900	Tentalive Test Method for Pullout Strength of Hardened Concrete
D7 5	Standard Methods of Sampling Aggregates
D1411	Standard Test Methods for Water-Soluble Chlorides Present as Admixes in Graded Aggregate Road Mixes
E4	Standard Methods of Load Verification of Testing Machines
E11	Standard Specification for Wire-Cloth Sieves for Testing Purposes
E12	Standard Definitions of Terms Relating to Density and Specific Gravity of Solids, Liquids, and Gases
E329	Standard Recommended Practice for Inspection and Testing Agencies for Concrete, Steel, and Bituminous Materials as Used in Construction
~	Manual of Aggregate and Concrete Testing

APPENDIX A - APPLICABLE ASTM STANDARDS (1)
Annual Book of ASTM Standards - Part 15

ASTM DESIGNATION

TITLE

D3398

Standard Test Method for Index of Aggregate Particle Shape and Texture

⁽¹⁾ American Society for Testing and Materials (ASTM), 1916 Race Street, Philadelphia, PA 19103

⁽²⁾ Use latest edition

ASTM DESIGNATION	TITLE
D152	Standard Test Methods for Chloride Ion in Water and Waste Water
D516	Standard Test Methods for Sulfate Ion in Water and Waste Water
D1988	Standard Test Method for Particulate and Dissolved Matter, Solids, or Residue in Water

⁽¹⁾ American Society for Testing and Materials (ASTM), 1916 Race Street, Philadelphia, PA 19103

⁽²⁾ Use latest edition

APPENDIX B - STANDARDS, GUIDES, AND RECOMMENDED PRACTICES

OF THE AMERICAN CONCRETE INSTITUTE (1)

ACI COMMITEE (2)	TITLE
116	- Cement and Concrete Terminology
201	- Guide to Durable Concrete
201	- Guide for Making a Condition Survey of Concrete in Service
211	 Recommended Practice for Selecting Proportions for Normal and Heavyweight Concrete
211	 Recommended Practice for Selecting Proportions for Structural Lightweight Concrete
212	- Guide for Use of Admixtures in Concrete
212	- Admixtures for Concrete
213	- Guide for Structural Lightweight Aggregate Concrete
214	- Recommended Practice for Evaluation of Strength Test Results of Concrete
221	- Selection and Use of Aggregates for Concrete
301	- Specifications for Structural Concrete for Buildings
304	- Recommended Practice for Measuring, Mixing, Transporting, and Placing Concrete
304	- Preplaced Aggregate Concrete for Structural and Mass Concrete
304	- Placing Concrete by Pumping Methods
304	- Placing Concrete With Belt Conveyors
305	- Hot Weather Concreting
306	- Cold Weather Concreting
308	- Recommended Practice for Curing Concrete
309	- Recommended Practice for Consolidation of Concrete

⁽¹⁾ American Concrete Institute, P.O. Box 19150, Redford Station, Detroit, Michigan 48219.

⁽²⁾ See latest edition of ACI Manual of Concrete Practice.

APPENDIX B - STANDARDS, GUIDES, AND RECOMMENDED PRACTICES

OF THE AMERICAN CONCRETE INSTITUTE (Continued)

ACI COMMITTEE	TITLE
311	- Recommended Practice for Concrete Inspection
311	- ACI Manual of Concrete Inspection
315	- Manual of Standard Practice for Detailing Reinforced Concrete Structures
318	- Building Code Requirements for Reinforced Concrete
318	- Commentary on Building Code Requirements for Reinforced Concrete
347	- Recommended Practice for Concrete Formwork
347	- Precast Concrete Units Used as Forms for Cast-in-Place Concrete
357	- Guide for the Design and Construction of Fixed Offshore Concrete Structures
503	- Use of Epoxy Compounds With Concrete
503	 Standard Specification for Bonding Hardened Concrete, Steel, Wood, Brick, and Other Materials to Hardened Concrete With a Multi-Component Epoxy Adhesive
503	 Standard Specification for Bonding Plastic Concrete to Hardered Concrete With a Multi-Component Epoxy Adhesive
503	- Standard Specification for Repairing Concrete With Epoxy Mortars
504	- Guide to Joint Sealants for Concrete Structures
506	- Recommended Practice for Shotcreting
506	- Specification for Materials, Proportioning, and Application of Shotcrete
515	- Guide for the Protection of Concrete Against Chemical Attack by Means of Coatings and Other Corrosion-Resistant Materials
517	- Recommended Practice for Atmospheric Pressure Steam Curing of Concrete

APPENDIX B - STANDARDS, GUIDES, AND RECOMMENDED PRACTICES

The second secon

OF THE AMERICAN CONCRETE INSTITUTE (Continued)

ACI COMMITTEE	TITLE
533	- Selection and Use of Materials for Precast Concrete Wall Panels
534	- Fabrication, Handling, and Erection of Precast Concrete Wall Panels
546	- Guide for Repair of Concrete Bridge Superstructures

AFPENDIX C - OTHER APPLICABLE STANDARDS, GUIDES AND RECOMMENDED PRACTICES

- "Rules for the Design, Construction, and Inspection of Offshore Structures," Det Norske Veritas, Oslo, 1377.
- "Guidelines for the Design, Construction, and Classification of Floating Concrete Structures," Det Norske Veritas, Oslo, 1978.
- "Recommendations for the Design and Construction of Concrete Sea Structures," Federation Internationale de la Precontrainte, Wexham Springs, 1977.
- 4. Allen, R.T.L. and Gregory-Cullen, J., "Inspection, Maintenance, and Repair of Concrete Offshore Structures," RR SMT-7401, Cement and Concrete Association, London, 1974.
- 5. "Design and Control of Concrete Mixtures," 12th Edition, Portland Cement Association, Skokie, Illinois, 1979, 133 pp.
- 6. "Certification of Ready Mixed Concrete Production Facilities," National Ready Mixed Concrete Association, Silver Spring, Maryland, 1976.
- 7. *Truck Mixer and Agitator Standards of the Truck Mixer Manufacturers Bureau, Truck Mixer Manufacturers Bureau, Silver Spring, Maryland, 1971.
- 8. "Manual of Standard Practice," Concrete Reinforcing Steel Institute, Chicago, 1976.
- 9. "Manual of Standard Practice Welded Wire Fabric," Wire Reinforcement Institute, Inc., McLean, Virginia, 1979.
- "Reinforcing Steel Welding Code," American Welding Society, AWS D12.1-75, Miami, Florida, 1975.
- 11. "PTI Post-Tensioning Manual," Post-Tensioning Institute, Phoenix, Arizona, 1981.

South marsh by Oak of the

· / / ...

APPENDIX D - ABBREVIATIONS

ABS - American Bureau of Shipping

ACI - American Concrete Institute

ASTM - American Society for Testing and Materials

AWS - American Welding Society

DNV = Det Norske Veritas

FIP * Federation Internationale de la Precontrainte

NRMCA - National Ready Mixed Concrete Association

PCA = Portland Cement Association

PTI - Post-Tensioning Institute

TMMB - Truck Mixer Manufacturers Bureau